

Specification YS\_v20

# YARDMASTER® INCLINED SCREW SEPARATOR

- The Yardmaster screw separator is designed to separate solids out of liquid
- Reduces bad odours, settlement in the lines
- Cleaner systems
- Can use separated water for wash down
- No blockages at irrigator
- More efficient pumping
- Reuse solids for fertiliser
- Designed and manufactured in New Zealand for New Zealand conditions



## Ideal for...

Dairy farms, paper mills, food industry, abattoirs, wineries, piggeries and poultry and waste water treatment

## Technical Specifications

Model	Screen Size (mm)	Screen Type	Capacity (m <sup>3</sup> /hr) <10% solids loading	Motor Size (kW)	Weight (approx kg)	Dimensions (WxDxH mm)
YS200C	2 <sup>s</sup> ,3,4	Perforated Mesh	Up to 25*	2.2	375	1380x1800x1580
YS200	2 <sup>s</sup> ,3,4	Perforated Mesh	Up to 30	3	620	1400x4250x3140
YS300	2 <sup>s</sup> ,3,4	Perforated Mesh	Up to 40	4	835	1800x4000x3300

\* Grass fed only, <sup>s</sup> Stainless steel

Specifications are subject to change without notice

## Applications & Case Studies



- CS\_CRA01**  
YS300 separator
- CS\_HED01**  
YS200mini separator
- CS\_BEN01**  
YS300 separator, transferring into spreading wagon
- CS\_SCA01**  
YS200 separator

